

400i

Introducing

iFume

The Future of Fume Extraction...



 **PUREX**
FUME EXTRACTION SYSTEMS



Features & Performance...

- Gas and particle sensors in the exhaust deliver an industry leading safety feature as standard.
- Patented quick change, high performance Labyrinth pre-filters deliver exceptional filter life.
- Purex only use the highest H14 grade HEPA filters available. Submicronic (HEPA) filtration removes 99.997% of particles down to 0.3 microns in size.
- Specially formulated activated carbon filtration removes a wide range of harmful gases.
- Purex units are simple to install and quiet in operation with low capital and running costs.
- High performance, continuous run, brushless motors ensure longevity and are maintenance free.
- Machines are precision made from brushed stainless steel and are mounted on castors for ease of mobility.

Operates Worldwide

90V - 253V operation anywhere in the world with no loss of performance.



Model	400i
Laser Coding	1704022
Voltage V	90-253
Wattage kW	1.1
Frequency Hz	50/60
Height mm	1070
Width mm	465
Depth mm	530
Weight Kg	60
Sound dBA*	55
Airflow m3/hr**	400
Pressure kPa**	11.0
IP Rating	54

< Volume Control

Includes:

- 1 x Main filter
- 1 x Labyrinth pre-filter
- 1 x Connection kit
- 1 x Power cable
- 1 x Operating Manual


* Under normal operation

** Maximum motor capacity

iFume Operating System...

“The new iFume operating system has been designed from the ground up to provide class leading performance and features, based on what our customers told us they wanted to see. iFume adds value to your business by improving overall equipment effectiveness (OEE) and filter life.”

Trefor Jones, Managing Director



Features

Motor Run Signal

Driven by the physical rotation of the impeller for industry leading performance & safety.

Hose Blocked Alarm

To minimise loss of production the alarm sounds if the hose becomes blocked.

Door Open Alarm

Door interlocks ensure the safety of the operator and protects the process.

Airflow


The flow rate can be set and the iFume operating system automatically compensates for minute changes in operating conditions to maintain the desired airflow.

Motor % Speed

Shows you how much power is in use. E.g. 30% is in reserve to overcome resistance to airflow as filters become blocked. This delivers longer filter life.

Temperature Monitoring

With safety cutouts to ensure the machine runs at a safe working temperature.



Remote Interface

The iFume can be controlled and monitored by the laser, locking out any screen adjustment.

Anti-Tamper System

Maximises efficiency by ensuring the set parameters are maintained.

Individual Filter Monitoring

Tells you precisely which filter requires replacing and (for additional safety) if gas or particles are bypassing the filters.

Ensures filter life is maximised and changeover time is minimised.

Support

Contacts and machine data are held in the data log.



Filters For Lasers...

Labyrinth Pre-filter: (For large particulate)

- F6 (standard)

Single:
111057

Main Filter: (For small particulate & gas)

- HEPA / Chemical PUR800

Single:
113505

Standard Connection Kit

- 50mm x 6.0m hose kit

Single:
100043

Power Cable

- UK - 410162
- Europe - 410163
- USA/Asia 120V - 410160
- USA/Asia 230V - 410161
- Australia - 410164
- No plug - 410165

Other filters and connection kits are available if required.

Options...

Remote ON/OFF Switch

Manually operated switch with a 5m cable. 105114

Clean Air Exhaust Cowl

Allows exhaust air to be vented to the outside of the building or it can be used to provide purified cooling air to (for example) a fan on a laser, printer, etc 190101

Interface Cable


8 core cable 5m long. 105147

Purex International Ltd.

QWP House
Capitol Park, Thorne,
Doncaster, DN8 5TX.
T: +44 (0)1405 746030
F: +44 (0)1405 746047
E: purex@purex.co.uk
W: www.purex.co.uk

Registered Office. Purex International Ltd. QWP House, Capitol Park, Thorne,
Doncaster DN8 5TX. Registered No. 5136616 England.
VAT No. GB842 5025 49 • WEEE Producer Registration Number: WEE/
CE0067TX

Layout...



Legend:

- 1) Air inlet - 80mm safe seal
- 2) Pre-filter
- 3) Main Filter (HEPA location)
- 4) Main Filter (Carbon location)
- 5) Clean air returned to workplace
- 6) Filter locking handle
- 7) Filter identification label

Pre-filter



Main Filter




All machines are mounted on four castors for increased mobility.

Interface Cable

Communicates with the laser using a 5m cable.

- Start/Stop Control
- Filter Blocked Warning
- Motor Run Signal



Distributed by...